FULL RANGE CEILING SPEAKER



- 5" Full-Range 8Ω Speaker
- Exceptional Voive & Music Reproduction
- Powering Mode: Full Range Passive
- For Permanent Installation

Product Information

CT5 is designed for vocal and music reproduction. The main features that countersign this product are: 130 mm (5") 2-way coaxial with waterproofed membrane to exponential profile, low distortion, extremely linear frequency response in vocal range, elevated dispersion, coated painted steel grille, easy fixing with soft torsion in box steel for ceiling. CT5 uses three positions line transformer for fittings to costant v o l t a g e .

Data Sheet

Frequency Response	±5 dB 100 Hz ~ 20 KHz -10 dB 70 Hz
Sensitivity (1 Watt @ 1 m) Max SPL Calculated	88 dB 101 dB
Nominal Input Impedance (Ω)	8 Ω
Power Handling (Watts Cont. AES) Peak Power Transformer Tapings 100V Line, Wa	20 W 80 W 20 - 10 - 5 W
Nominal Dispersion (@ -6 dB)	100° (H) x 100° (V)
Dimensions mm (±1 mm) (H x D)	202 x 87
Weight	1.5 Kg



- Plastic Baffle, Metal Driver Chassis, Metal Grille
- Finish: White or Black
- Connectors: Multi Clamps



FRONT



6.7 cm



INSTALL | EVENTS

20.25 cm